

TECHNICAL DATA SHEET

Issue Date: 12-JULY-22

Revision Date: 12-JULY-22

Alt. Identifier: BLSTX-OBL

DESCRIPTION: BallistiX Obliterate

BallistiX OBLITERATE is a concentrated formula that provides deep penetrating and lifting action to remove rigid surface contaminants. Its penetrating and cleaning act is effective on oily residues and surface soiling contaminants. This cleaner contains a blend of highly active components, which are very effective for most general cleaning purposes. For maximum efficiency, this concentrated formula should be diluted with clean, hot water before use.

OBLITERATE is an effective surface preparation cleaner for numerous interior and exterior surfaces; HVAC/R coils & cabinets, hard tile & grout, terrazzo, concrete, aluminum, copper, brass, bronze, stainless steel, painted surfaces, etc. OBLITERATE is also the recommended cleaner for the post-maintenance cleaning of HVAC/ R Coils treated with OBLITERATE.

DILUTION INSTRUCTIONS

BallistiX OBLITERATE is a **CONCENTRATE** packaged in one-gallon and five-gallon containers. Using the ratios provided below, dilute the product with clean, hot water.

HVAC/R Coils & Cabinets – 1 part OBLITERATE to 1 part water
Ceramic Tile & Grout – 1 part OBLITERATE to 1 part water
Concrete or Epoxy Terrazzo – 1 part OBLITERATE to 1 part water
Mold & Mildew Spores – 1 part OBLITERATE to 5 parts water & 1 part bleach
Polished Metal & Bright Works – 1 part OBLITERATE to 20 parts water
Un-polished Non-ferrous Metals – 1 part OBLITERATE to 1 part water
Painted Surfaces – 1 part OBLITERATE to 20 parts water
Fiberglass & Gel Coat – 1 part OBLITERATE to 5 parts water
Post-Cleaning HVAC/R Coils – 1 part OBLITERATE to 20 parts water

While these ratios are good as a "rule of thumb", various applications may require more or less OBLITERATE. Alter the ratio as needed. Utilizing hot water will increase the cleaning efficiencies of OBLITERATE. Always wear protective glasses and latex gloves.

NOTE: Always try the diluted mixture on a small test area to determine if the dilution ratio is correct for the cleaning requirement. Never exceed 1:1 dilution strength.

2. DIRECTIONS FOR USE

DIRECTIONS FOR USE: Apply OBLITERATE using a pump-spray applicator and allow the product to 'sit' for 3 to 5 minutes. Then using a swing machine with a black pad or clean-grit or nylo-grit brush, agitate the surface. Repeat the above process as necessary until the surface is clean - free from contaminants. For smaller flooring surfaces, a scrub brush on an extension handle can be used. Pick up residue with rinse & vacuum reclaim extraction equipment.

3. JOB SITE SAFETY

JOB SITE SAFETY: It is highly recommended to wear safety glasses and latex gloves when working with OBLITERATE. Be sure to read specific label cautions and MSDS before working with any BallistiX products.